

# OTTAWA RANGE



**SENTINEL**  
CAST IRON & STEEL STOVES

Great value. Great warmth.



## OTTAWA SQUARE 12

Heat output **12KW – 450m<sup>3</sup>**

Flue outlet **150mm**

Top & rear flue outlet

Dimensions **H610mm x W584mm x D420mm**

Stove height with log stand **850mm**

Rear flue centre height

- without log stand **480mm**

- with log stand **730mm**

  
75% EFFICIENCY



## OTTAWA CURVE

Heat output **10KW – 380m<sup>3</sup>**

Flue outlet **150mm**

Top & rear flue outlet

Dimensions **H620mm x W520mm x D450mm**

Stove height with log stand **820mm**

Rear flue centre height

- without log stand **490mm**

- with log stand **690mm**

  
85% EFFICIENCY



## OTTAWA SQUARE 8

Heat output **8KW – 300m<sup>3</sup>**

Flue outlet **125mm**

Top & rear flue outlet

Dimensions **H530mm x W500mm x D300mm**

Stove height with log stand **730mm**

Rear flue centre height

- without log stand **435mm**

- with log stand **635mm**

  
80% EFFICIENCY

## OTTAWA RANGE



### OTTAWA COMPACT

Heat output **6KW – 220m<sup>3</sup>**

Flue outlet **125mm**

Top & rear flue outlet

Dimensions **H560mm x W480mm x D365mm**

Stove height with log stand **750mm**

Rear flue centre height

- without log stand **460mm**

- with log stand **650mm**

  
85% EFFICIENCY



### OTTAWA DS TUNNEL (DOUBLE-SIDED)

Heat output **11KW – 420m<sup>3</sup>**

Flue outlet **125mm**

Top flue outlet

Dimensions **H570mm x W580mm x D420mm**

  
81% EFFICIENCY



### OTTAWA MARVIC 550 (INSERT)

Heat output **8KW – 300m<sup>3</sup>**

Flue outlet **125mm**

Top flue outlet

Dimensions **H482mm x W570mm x D344mm**

Frame dimensions **H571 x W639**

Black trim glass door

  
76% EFFICIENCY



### OTTAWA MARVIC 700 (INSERT)

Heat output **11KW – 418m<sup>3</sup>**

Flue outlet **125mm**

Top flue outlet

Dimensions **H482mm x W700mm x D344mm**

Frame dimensions **H571 x W789**

Black trim glass door

  
76% EFFICIENCY

## OTTAWA MARVIC 950

*Defined by its sleek 950mm-wide landscape format, the Marvic 950 range is designed to stand out in any space. Single- and double-sided models can be installed as either freestanding units (on a log box or plinth) or as insert fireplaces with finishing frame.*

Heat output **15KW – 563m<sup>3</sup>**

Flue outlet **150mm**

Top flue outlet

Dimensions **H535mm x W950mm x D480mm**

With log box **H785mm x W950mm x D480mm**

With frame **H600mm x W994mm**

  
80% EFFICIENCY



### SINGLE-SIDED (INSERT / FREE-STANDING)



### DOUBLE-SIDED (INSERT / FREE-STANDING)



## **Warmth, Comfort and Enduring Style**

*The Ottawa Range is a carbon-neutral collection designed for efficient, controlled heat. Hand-constructed for durability and consistent performance, each stove combines clean-burning technology with a pre-heated air wash system to maintain a clear view of the fire. The range includes freestanding, insert and extra-wide landscape models, with selected units offering dual flexibility as either freestanding or insert installations. Contemporary styling and clean lines make it suitable for both traditional and modern interiors.*

### ***Advanced Clean Burn System***

***Pre-Heated Air Wash***

***Multi-Fuel Capability***

***Freestanding, Insert and Extra-Wide Options***

***Thick Steel Plate Construction***

***Cast Iron Door, Grate and Log Retainer  
Across the Entire Range***



DISTRIBUTED BY



[WWW.WOODSTOVEFIREPLACES.CO.ZA](http://WWW.WOODSTOVEFIREPLACES.CO.ZA)